Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Deko-Light

Supplier's address: Product Management, Deko-Light Elektronik Vertriebs GmbH, Auf der Hub 2,

D-76307 Karlsbad, DE

Model identifier: 565155

Type o	of light	source:
--------	----------	---------

Lighting technology used:	LED	Non-directional or directional:	DLS	
Light source cap-type	other electrical			
(or other electric interface)				
Mains or non-mains:	NMLS	Connected light source (CLS):	Nein	
Colour-tuneable light source:	Nein	Envelope:	-	
High luminance light source:	Nein			
Anti-glare shield:	Nein	Dimmable:	Only with specific dimmers	
Product parameters				

Product parameters

Parameter	Value	Parameter	Value		
General product parameters:					
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer	7	Energy efficiency class	G		
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	560 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000		
On-mode power (P _{on}), expressed in W	7,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00		
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80		

Outer	Height	24	Spectral power	See image	
dimensions	Width	110	distribution in the	in last page	
without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Depth	110	range 250 nm to 800 nm, at full-load		
Claim of equiva	lent power ^(a)	-	If yes, equivalent power (W)	-	
			Chromaticity	0,382	
			coordinates (x and y)	0,380	
Parameters for directional light sources:					
Peak luminous i	ntensity (cd)	192	Beam angle in degrees, or the range of beam angles that can be set	113	
Parameters for LED and OLED light sources:					
R9 colour rende	ring index value	19	Survival factor	0,90	
the lumen main	tenance factor	0,70			

(a)'-': not applicable; (b)'-': not applicable;

