

Artikel Nr.: 110010

Deckeneinbauring, Mizar I, Weiß-matt, 12V AC/DC, 1x max. 35,00 W



Technische Daten

Charakteristik

Material	Aluminium Druckguss
Farbe	Weiß-matt
Optik	
im Lieferumfang	inklusive GU5,3 Fassung mit 15cm Kabel IP 44 nur im eingebauten Zustand



Elektrische Daten

Leistung	1x max. 35,00 W
Eingangsspannung	12V AC/DC
Eingangsstrom	
Fassung / Sockel	GU5.3 / MR16
Anzahl Sockel	1
Netzgerät	exkl. Trafo
Ansteuerung	dimmbar über optionales Leuchtmittel
Anschlussmöglichkeit	offene Kabel
Schutzklasse I, II, III	III




Artikel Nr.: 110010

Deckeneinbauring, Mizar I, Weiß-matt, 12V AC/DC, 1x max. 35,00 W



Lichtrichtung

Dreh- und Schwenkbereich	feststehend
Neigungswinkel	
Abstrahlverhalten	
Reflektor / Linse	



Abmessungen und Gewicht

Länge	
Breite	
Höhe	41 mm
Durchmesser	85 mm
Einbautiefe	90 mm
Gewicht	140 g

Ausschnittsmaß

Länge	
Breite	
Durchmesser	72 mm





Artikel Nr.: 110010

Deckeneinbauring, Mizar I, Weiß-matt, 12V AC/DC, 1x max. 35,00 W



Grenzwerte

Betriebstemperatur	-5°C - +40°C
Lagertemperatur	-10°C - +40°C
IP - Schutzart	IP 44

EEL	Die Leuchte ist geeignet für Leuchtmittel der Energieeffizienzklassen A++ bis E
IP 44	Schutz gegen das Eindringen von Fremdkörper > 1 mm. Geschützt gegen Spritzwasser.
	Leuchte der Schutzklasse III Leuchte, bei der der Schutz gegen elektrischen Schlag auf der Anwendung der Schutzkleinspannung (SELV) beruht und in der Spannungen höher als SELV nicht erzeugt werden.
	Aufgrund des komplexen Herstellungsprozesses von LED stellen die angegebenen Werte nur rein statistische Größen dar und müssen nicht zwingend den tatsächlichen Parametern jedes einzelnen LED-Moduls entsprechen, sondern können von den typischen Werten abweichen.

Article no.: 110010

Built in ceiling lamp, Mizar I, matt white, 12V AC/DC, 1x max. 35,00 W



Technical Data

General Characteristics

Material	aluminum die casting
Colour	matt white
Optics	
included in delivery	inclusive socket GU5,3 with 15cm cable IP 44 only in build in situation



Electrical Characteristics

Power	1x max. 35,00 W
input voltage	12V AC/DC
input current	
Base (standard designation)	GU5.3 / MR16
Number of bases	1
Power supply unit	excl. transformer
Electronically reversible	dimnable via optional bulb
Connection possibility	wire with open ends
Protection class I, II, III	III




Article no.: 110010

Built in ceiling lamp, Mizar I, matt white, 12V AC/DC, 1x max. 35,00 W



Light Direction

Rotating and tilting range	fixed
Angle of inclination	
Radiation direction	
Reflector / lense	



Dimensions & Weight

Length	
Width	
Height	41 mm
Diameter	85 mm
Mounting Depth	90 mm
Product Weight	140 g

Cut-out dimensions

Length	
Width	
Diameter	72 mm



Article no.: 110010

Built in ceiling lamp, Mizar I, matt white, 12V AC/DC, 1x max. 35,00 W



Absolute maximum ratings

Working temperature	-5°C - +40°C
Storage temperature	-10°C - +40°C
IP - Code	IP 44

EEl The luminaire is suitable for lamps of energy efficiency classes A++ to E.

IP 44 Protection against penetration of foreign objects > 1 mm. Protection against penetration of splashing water.



Lightings of Protection Class III
Luminaire in which protection against electric shock relies on supply at safety extra-low voltage (SELV) and in which voltages higher than those of SELV are not generated.



Because of the complex manufacturing process of the LED the above shown data are just a statistical size, which is not forced to be the realistic data of every LED.